



Cobra Laning System



Features

- No stopping or slowing of containers - true "switch-on-the-fly" motion
- At product changeover, discharge lane centers update automatically and the product width adjustment is manual and tool-less
- Low friction rail surface has a long life - no product damage
- High speed applications
- Minimal mechanical complexity - the simplicity makes it ultra reliable
- Machine can lane into an infinite number of lanes with a maximum center to center distance of outside lane to outside lane of 21.9 inches [556mm] for a 66 inch [1,676mm] wide machine and 37.4 inches [950mm] for a 78 inch [1,981mm] wide machine

Cobra Laning System

When you watch the Cobra Laning System in action, it is easy to see how it got its name! BW Container Systems' Cobra Laning System provides a smooth transfer of products from single file to multiple lanes, continuously and accurately. Like its serpentine namesake, the Cobra laner's snake-like guide rail remains docile while delivering containers to a chosen lane, but snaps into action when it is time to switch lanes. The result is high speed and accurate product placement at line speed without stopping the infeed product flow or the upstream equipment. The Cobra Laning System assures reliable, smooth and damage-free product transfers with no container tipping. The Cobra Laning System also takes a bite out of down time and handles a multitude of containers and conditions. The maximum laneable product width is 14 inches [356mm] but wider products can flow straight through the machine.

Contact our experienced sales teams today for a comprehensive review of your application(s) and to see how our Cobra Laning System can benefit your company.



Glass bottles being laned



For our European office, contact:
Plumtree Farm Industrial Estate,
Bircotes, Doncaster
South Yorkshire DN11 8EW ENGLAND
t. +44 (0) 1302 711056

Ambec CBI-Fleetwood Fleetwood Goldco-Wyard

BW Container Systems

1305 Lakeview Drive
Romeoville, IL 60446 USA

t. +1 (630) 759-6800
bwcontainersystems.com

